

APPENDIX TO MARCH 27, 2006 AMENDMENT
Patent Application No.: 10/041,082

Copy of Interview Discussion Outline Submitted by E-mail to
Examiner on March 21, 2006 prior to the Interview

BEST AVAILABLE COPY

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

RECEIVED
CENTRAL FAX CENTER
MAR 27 2006

Attorney Docket No.: HA-87 (HAL-ID 202)

Appl. No.: 10/041,082

Applicant: Carl SCARPA

Filed: January 7, 2002

Title: CHANNEL ESTIMATION AND COMPENSATION TECHNIQUES FOR USE IN
FREQUENCY DIVISION MULTIPLEXED SYSTEMS

TC/A.U.: 2661

Examiner: IAN MOORE

Mail Stop Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

INTERVIEW OUTLINE

Sir:

This interview outline is being submitted to assist the Examiner in preparing for the March 21, 2006 in-person interview scheduled for 2 pm.

Amendments to the Claims appear in the listing of claims which begins on page 2 of this paper.

Remarks/Arguments begin on page 11 of this paper.

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

This listing of claims will replace all prior versions, and listings, of claims in the application:

1 Claim 1 (original): A method of processing a frequency
2 division multiplexed signal including a plurality of tones,
3 the method comprising:
4 receiving said frequency division multiplexed
5 signal; and
6 performing a constant modulus based update
7 operation to update a channel estimate corresponding to at
8 least one tone of the frequency division multiplexed
9 signal.

1 Claim 2 (currently amended): The method of claim 1,
2 further comprising:
3 using the updated channel estimate to perform a
4 channel compensation operation on a portion of the
5 frequency division multiplexed signal corresponding to said
6 at least one tone.

1 Claim 3 (original): The method of claim 1, further
2 comprising:
3 performing a reduced constellation decision
4 directed update operation to update said channel estimate.

1 Claim 4 (original): The method of claim 3, further
2 comprising:
3 performing a full constellation decision directed
4 update operation to update said channel estimate.

1 Claim 5 (original): The method of claim 4, further
2 comprising:

*** SUBMITTED FOR DISCUSSION PURPOSES ***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

3 receiving, as part of said frequency division
4 multiplexed signal, a pilot transmitted on said at least
5 one tone; and
6 using said received pilot to update said channel
7 estimate.

1 Claim 6 (original): The method of claim 1, further
2 comprising:
3 generating a signal noise measurement value for
4 said at least one tone;
5 comparing the signal noise measurement value to a
6 first threshold; and
7 selecting a channel estimate update method, as a
8 function of the comparison of the signal noise measurement
9 value to the first threshold, from a plurality of different
10 channel estimation update methods.

1 Claim 7 (original): The method of claim 6, wherein the
2 plurality of different channel estimation update methods
3 include at least one of a constant modulus based update
4 method and an interpolated pilot value based method.

1 Claim 8 (original): The method of claim 6, wherein the
2 plurality of different channel estimation update methods
3 include at least one of a reduced constellation decision
4 directed update method and a full constellation decision
5 directed update method.

1 Claim 9 (original): The method of claim 6, further
2 comprising:
3 when said comparison of the signal noise
4 measurement value to the first threshold indicates that the

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

5 signal noise measurement value does not exceed said first
6 threshold,
7 comparing the signal noise measurement value to a
8 second threshold; and
9 wherein the step of selecting a channel estimate
10 update method is also performed as a function of the
11 comparison of the signal noise measurement value to the
12 second threshold.

1 Claim 10 (original): The method of claim 9, wherein a
2 reduced constellation decision directed channel estimate
3 update method is selected when the comparison of the signal
4 noise measurement value to the second threshold indicates
5 that the signal noise measurement value exceeds the second
6 threshold and wherein a full constellation decision
7 directed channel estimate update method is selected when
8 the comparison indicates that the signal noise measurement
9 value is below the second threshold.

1 Claim 11 (original): The method of claim 1, further
2 comprising:
3 performing a decision directed channel estimate
4 update operation to update a channel estimate corresponding
5 to a second tone of the frequency division multiplexed
6 signal at the same time said constant modulus based update
7 operation is performed.

1 Claim 12 (original): A method of updating channel
2 estimates corresponding to different tones of an orthogonal
3 frequency division multiplexed communications signal, the
4 method comprising, for each of at least two tones of the
5 communications signal, performing the steps of:

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

6 generating a signal noise measurement for the
7 tone,
8 selecting a channel estimate update method for
9 the tone, from a set of at least three different channel
10 estimate update methods, based on a comparison of the
11 generated signal to at least one threshold; and
12 updating a channel estimate for the tone using
13 the selected channel estimate update method.

1 Claim 13 (original): The method of claim 12, wherein the
2 set of at least three different channel estimate update
3 methods includes a reduced constellation decision directed
4 update method.

1 Claim 14 (original): The method of claim 13, wherein the
2 set of at least three different channel estimate update
3 methods further includes a constant modulus based channel
4 estimate update method.

1 Claim 15 (original): The method of claim 14, wherein the
2 set of at least three different channel estimate update
3 methods further includes a full constellation decision
4 directed update method and an interpolated pilot based
5 channel estimate update method.

1 Claim 16 (original): The method of claim 12, wherein the
2 set of at least three different channel estimate update
3 methods includes a constant modulus based channel estimate
4 update method.

1 Claim 17 (original): The method of claim 16, further
2 comprising the step of using the updated channel estimate

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

3 generated for each of the tones to perform a channel
4 compensation operation.

1 Claim 18 (original): A method of updating a channel
2 estimate for a carrier signal of an orthogonal frequency
3 division multiplexed communications signal, the method
4 comprising:
5 receiving the carrier signal; and
6 performing a reduced constellation decision
7 directed channel estimate update operation, using the
8 received carrier signal, to update said channel estimate.

1 Claim 19 (original): The method of claim 18, further
2 comprising:
3 after performing said reduced constellation
4 decision directed channel estimate update operation
5 performing a full constellation decision directed channel
6 estimate update operation.

1 Claim 20 (original): The method of claim 19, further
2 comprising:
3 generating a signal noise measurement;
4 comparing the signal noise measurement to a
5 threshold; and
6 using the results of the comparison to determine
7 when to switch from performing said reduced constellation
8 decision directed channel estimate update operation to
9 performing the full constellation decision directed channel
10 estimate update operation.

1 Claim 21 (original): A method of updating a channel
2 estimates for carrier signals of an orthogonal frequency

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

3 division multiplexed communications signal, the method
4 comprising:
5 receiving the carrier signals; and
6 performing a reduced decision directed channel
7 estimate update operation, for at least a first plurality
8 of the received carrier signals of said orthogonal
9 frequency division multiplexed communications signal.

1 Claim 22 (original): The method of claim 21, further
2 comprising:
3 comparing a signal noise value to a threshold;
4 and
5 selecting for at least one of said received
6 carrier signals, as a function of said comparison, between
7 performing a decision directed channel estimate update
8 operation and performing a constant modulus based channel
9 estimate update operation.

1 Claim 23 (original): The method of claim 22, wherein a
2 constant modulus based channel estimate update operation is
3 performed for one carrier signal at the same time a reduced
4 decision directed channel estimate update operation is
5 performed for another carrier signal.

1 Claim 24 (original): A method of updating first and second
2 channel estimates corresponding to a first and a second
3 carrier frequency of an orthogonal frequency division
4 multiplexed signal, the method comprising:
5 generating first and second signal noise measurements
6 for the first and second carrier frequencies, respectively;
7 independently comparing each of the first and second
8 signal noise measurements to at least one noise threshold

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

9 to independently select a channel estimate update method to
10 be used to update the first and second channel estimates,
11 respectively the channel estimate update methods including
12 at least one of an amplitude only update method and a
13 reduced constellation decision directed update method.

1 Claim 25 (original): The method of claim 24, wherein the
2 first and second signal noise measurements are signal to
3 noise ratio measurements and where the first threshold is a
4 first signal to noise ratio threshold

1 Claim 26 (original): A receiver apparatus for receiving
2 and processing an orthogonal frequency division multiplexed
3 signal, the apparatus comprising:
4 a carrier recovery module for performing a
5 carrier recovery operation on the multiplexed signal;
6 a channel compensation module coupled to the
7 carrier recovery circuit for performing channel
8 compensation operation on each tone of the orthogonal
9 frequency division multiplexed signal;
10 a signal noise measurement module for generating,
11 for each tone, a signal noise measurement; and
12 a channel estimate update selection module for
13 selecting between an amplitude only channel estimate update
14 method and an amplitude and phase channel estimate update
15 method, for each individual tone, as a function of the
16 signal noise measurement generated by said signal noise
17 measurement module for the individual tone.

1 Claim 27 (original): The apparatus of claim 26, further
2 comprising:

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

3 means for generating an updated channel estimate
4 for each tone of the multiplexed signal as a function of
5 the selected channel estimate update method, coupled to
6 said channel compensation module and said channel estimate
7 update selection module.

1 Claim 28 (original): The apparatus of claim 27, wherein
2 the amplitude only channel estimate update method is a
3 constant modulus based channel estimate update method.

1 Claim 29 (original): The apparatus of claim 28, wherein
2 the amplitude and phase channel estimate update method is a
3 reduced constellation decision directed update method.

1 Claim 30 (original): An apparatus for updating channel
2 estimates in a frequency division multiplexed receiver, the
3 apparatus comprising:
4 a plurality of channel estimate update modules, said
5 plurality of channel estimate update modules including:
6 i) a constant modulus channel estimate update
7 module for performing a channel estimate update
8 for a tone of a frequency division multiplexed
9 signal using a constant modulus algorithm; and
10 ii) a full decision directed channel estimate
11 update module for performing a full decision
12 directed channel estimate update for a tone of a
13 frequency division multiplexed signal; and
14 a control module for selecting, as a function of a
15 signal measurement, one of said plurality of channel
16 estimate update modules to be used for performing a channel
17 estimate update operation.

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

1 Claim 31 (original): The apparatus of claim 30,
2 wherein said signal measurement is a signal noise
3 measurement, the apparatus further comprising a signal
4 noise measurement module coupled to said control module;
5 and
6 wherein said plurality of channel estimate update
7 modules further includes a reduced decision directed
8 channel estimate update module.

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

REMARKS/ARGUMENTS

Applicants respectfully submit that the outstanding rejections are all based under 35 U.S.C. §103 based on various Examiner proposed combinations of references which seem to fail to take into consideration the teachings of the references a whole.

Applicants representative intends to step through the applied references and rejections one by one and discuss what the references actually show and how the references do not teach or suggest the combinations asserted by the Examiner.

For example, with regard to the rejection of claims 1, 2, 5-7, 12, 17 and 25 the Examiner asserts these claims are unpatentable over the Wright patent in view of Rupp.

The cited portion of the Wright patent (col. 10 lines 24-32) describes the use of a channel estimator 320 which estimates the effects of the channel based on extracted pilot symbols.

The Examiner further cites col 13, lines 35-37 stating that the reference teaches "calculating a channel estimation and updating it periodically (column 10 lines 24-32) using techniques that are known in the art (column 13, lines 35-37)." (Office Action page 2)

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

The cited portion when considered in the slightly broader context of the full sentence provided at col. 13, lines 33-37 states:

The **extracted pilot symbols are then compared with their expected values** (i.e., their values prior to transmission over the wireless channel) **to perform channel estimation** and compensation using techniques that are known in the art. (Bold added for emphasis)

Accordingly, it is respectfully submitted that a fair reading of the Wright patent is that it is describing the use of channel estimation **based on extracted pilots which are compared to their expected values, this is a decision directed process** since it depends on a comparison between the extracted pilot symbol and the expect value. While various methods may be known for implementing such a decision directed channel estimation process, such methods are not any arbitrary known channel estimation technique or a constant modulus technique as the Examiner seems to suggest by citing RUPP.

Applicants argument that it would not be obvious or desirable to replace the decision directed process described in Wright with a constant modulus method is further supported by the statement at col 10, lines 24-25 of Wright which states "The channel estimator 520 **compares the amplitudes and phases** of the extracted pilot symbols with the expected **amplitudes and phases**, to thereby estimate the effects of the channel on the transmitted signal." The Wright patent indicates that

*** SUBMITTED FOR DISCUSSION PURPOSES***
NOT TO BE ENTERED AS A FORMAL AMENDMENT

this is used in determining the "phase impairment" in addition to "amplitude impairment".

Applicants respectfully submit that constant modulus algorithms do not provide information on phase impairment. (See Applicants application page 8 lines 3-9)

Accordingly, one of ordinary skill in the art reading the Wright patent would not be motivated to replace the decision directed system which provides both phase and amplitude information with one that provides simply amplitude information as would be the result if the decision directed technique of would not be motivated to replace the decision directed system which provides both phase and amplitude information with one that provides simply amplitude information as would be the result if the decision directed technique of Wright were replaced with a constant modulus method as the Examiner asserts would be obvious.

Applicants' representative intends to discuss the other references used to reject the claims during the interview as well and suggest the Examiner look over the cites to the Koslov patent in the office action and what is actually disclose in the applied patent.

Respectfully submitted,

Michael Straub

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.